

Type	Material	Rigid	Flexible	Quick Ship	Guarantee	UV Resistance	Temperature Range	Maximum Rec. Size	Holes
Plastic	Accu-Shield™ (XP)	☑			15 Year	15	-60° to 260°	48" x 96"	☑
	Reflecta-Shield™	☑			10 Year	10	-30° to 200°	48" x 72"	☑
	Lumi-Shield™	☑				5 - 7	-30° to 175°	24" x 36"	☑
	Plastic (VP)	☑		☑		1 - 3	-90° to 168°	36" x 48"	☑
	Plastic-Lite	☑		☑		3 - 5	0 to 160°	48" x 96"	☑
	Plastic Plus	☑				1 - 3	-90° to 168°	48" x 96"	☑
	Dura-Plastic™ (XT)	☑		☑	7 Year	7	-20° to 140°	24" x 36"	☑
	Dura-Shield™	☑				4 - 5	-40° to 175°	24" x 36"	on request
	Lite-Corr Plastic	☑				1 - 2	-17° to 160°	24" x 36"	on request
	Max Corrugated Plastic	☑				1 - 2	0 to 140°	48" x 96"	on request
	Lumi-Glow™ Plastic (GP)	☑		☑		3	-30° to 175°	24" x 48"	☑
	Lumi-Glow™ Plus+ Plastic	☑		☑		3 - 5	-50° to 190°	24" x 48"	☑
Metal	Galvanized Steel	☑			5 Year	5	-40° to 250°	48" x 96"	☑
	Aluminum (VA)	☑		☑	5 Year	5	-20° to 140°	48" x 96"	☑
	Heavy-Duty Aluminum	☑		☑	5 Year	5	-40° to 250°	48" x 96"	☑
	Max-Duty Aluminum	☑		☑	5 Year	5	-40° to 250°	48" x 96"	☑
	Engineer-Grade Reflective Aluminum	☑		☑	5 Year	5 - 7	-30° to 200°	36" x 48"	☑
	High-Intensity Reflective Aluminum	☑		☑	7 Year	7 - 10	-30° to 200°	36" x 48"	☑
	DG High-Prism Reflective Aluminum	☑		☑	7 Year	7 - 10	-30° to 200°	36" x 48"	☑
	Dura Lumi-Glow™ Aluminum	☑			5 Year	5	-30° to 175°	24" x 36"	☑
	Stainless Steel-Full Color	☑			10 Year	10	up to 200°	9" x 12"	☑
	Stainless Steel-Self Color	☑			15 Year	15	up to 200°	9" x 12"	☑
	Perma-Black™ Stainless Steel	☑			15 Year	15	up to 750°	20" x 24"	☑
	Perma-Black™ Aluminum	☑			10 Year	10	up to 700°	20" x 24"	☑
Composite	St ² Laser Signs	☑			Lifetime	Lifetime	up to 2000°	14" x 20"	☑
	Aluma-Lite™ (XL)	☑		☑	10 Year	10	-58° to 175°	48" x 96"	☑
	Max Aluma-Lite™	☑			10 Year	10	-58° to 175°	48" x 96"	on request
	Max Aluma-Wood	☑				3 - 5	-30° to 200°	48" x 96"	on request
FiberGlass	Fiberglass, Heavy-Duty Fiberglass, Deluxe Fiberglass	☑		☑		4 - 5	-65° to 212°	48" x 96"	☑
	Dura-Fiberglass™ (XF)	☑			10 Year	10	-20° to 140°	48" x 96"	☑
Adhesive	Polyester		☑	☑		2	-40° to 250°	18" x 24"	
	Lumi-Glow™ Flex (GF)		☑	☑		3	-30° to 175°	24" x 36"	
	Lumi-Glow™ Plus+ Flex		☑	☑	5 Year	5	-20° to 125°	24" x 36"	
	Adhesive Vinyl (VS)		☑	☑		2 - 4	-20° to 176°	36" x 48"	
	Adhesive Dura-Vinyl™ (XV)		☑	☑	5 Year	5	-20° to 176°	36" x 48"	
	Engineer-Grade Prismatic Adhesive Sheet		☑	☑	5 Year	5 - 7	-30° to 200°	36" x 48"	
Non-Adhesive	High-Intensity Prismatic Adhesive Sheet		☑		7 Year	7 - 10	-30° to 200°	36" x 48"	
	PF-Poly Paper		☑	☑		6 mos.	-60° to 200°	18" x 24"	
	Magnetic Co-Poly Vinyl		☑	☑		2 - 4	0 to 160°	24" x 48"	